

# LEDDriving SL W21W/5W RED

Ideal replacement for any vehicle




**Suitable for various vehicle exterior applications**

Available in Red




**Replaces conventional W21W/5W lamps**

Easy upgrade to LED technology with plug & play solutions



**Reliable OSRAM quality stands for less lamp replacements**

4-year OSRAM guarantee (refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions)



## Suitable LED replacement for W21/5W

LEDDriving SL W21W/5W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional W21W/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Technical data

### Product information

Order reference	7515DRP
Product type (off-road vs. on-road)	Off-road $\pm$ W21/5W
Application (Category and Product specific)	Mainly used for signal/ indicator applications


### Electrical data

Power input	2.4 W
Nominal voltage	12.0 V
Nominal wattage	1.70/0.40 W
Test voltage	13.5 V
Power input tolerance	$\pm 10$ %

### Photometrical data

Luminous flux	80/10 lm
Luminous flux tolerance	$\pm 25$ %
Light color LED	Red

### Dimensions & weight



Diameter	20.0 mm
Product weight	12.00 g
Length	47.5 mm

### Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

## Product datasheet

### Additional product data

Base (standard designation)	W3x16q
-----------------------------	--------

### Capabilities

Technology	LED <sup>1)</sup>
------------	-------------------

<sup>1)</sup> Light-emitting diode lamp

### Country specific categorizations




Order reference	7515DRP
-----------------	---------

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172152280	LEDiving SL $\triangle$ W21/5W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm <sup>3</sup>	36.25 g
4062172152297	LEDiving SL $\triangle$ W21/5W	Shipping carton box 10	115 mm x 105 mm x 145 mm	1.75 dm <sup>3</sup>	215.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File	
	Brochures LEDiving Retrofits - Exchange overview (EN)
	Brochures 618438_LEDiving RETROFIT application overview (EN)
	360 Degree Image LEDiving SL W215W 7515DRP-02B

#### Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### Application advice

## Product datasheet

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# OSRAM