

# LED work lamps with other holders

## TECHNICAL DATA / FEATURES

dimensions: 100x100x76  
 luminous flux of the LED module: 3000 lm, 2500 lm, 2000 lm, 1500 lm  
 luminous flux of the lamp: 2400 lm, 2000 lm, 1600 lm, 1200 lm  
 maximum power: 30W, 29W, 25W, 24W  
 nominal voltage: 12V-24V DC, 48V DC  
 permissible power supply voltage: 10.5V-30V DC, 40-60V DC  
 source of light: 6 x LED  
 colour temperature: 5000-7000K  
 light distribution angle: 66° x 20°  
 IP rating: IP67, IP69K  
 work temperature: -40°C - +80°C  
 housing's material: aluminium/plastic  
 lens' material: plastic  
 built-in connectors: AMP Faston 250  
 other: protection:  
     • against overheating  
     • against reverse polarisation  
     bracket made of Inox steel



## ADDITIONAL INFORMATION



Work lamps are used to illuminate working space near vehicles, tractors, slow-moving machines and any other places where indicated voltage is available.

The lamps comply with EMC Directive 2004/108/EC. They do not emit electromagnetic interference as well as they are resistant to its influence.

Correct polarity required.

Replacement parts:  
neodymium magnet φ89/500N (1 pc.) - cat. No. CAR4.51320

## DIMENSIONS



Cat. number	Luminous flux	IP rating	Accessories	Mounting method	Connectors
<b>LED9A.53795</b>	✓ 3000 lm	✓ IP67	✓ LED module 12V-24V	✓ any	AMP Faston 250
<b>LED9A.53796</b>	✓ 2500 lm	✓ IP69K	✓ LED module 48V	✓ installed vertically up	Deutsch DT
<b>LED6.49895</b>	✓ 2000 lm	✓	✓ handle	✓ rear	AMP SuperSeal 1.5
<b>LED6.49896</b>	✓ 1500 lm	✓	✓ cable 0,22 m		Cap / Pin
<b>LED6.49897</b>		✓	✓ cable 0,5 m		
LED6.49825		✓	✓ cable 8 m		
<b>LED2.47595</b>		✓	✓ switch		
<b>LED2.47596</b>		✓	✓ cigarette lighter plug		
LED2.47597					
LED2.47525					
<b>LED1.46831</b>					
<b>LED1.46832</b>					
LED1.46833					
LED1.46818					
LED1.46825					
<b>LED1.46834</b>					
<b>LED1.46835</b>					