Product datasheet

OSRAM

TRUCKSTAR PRO R5W

Brightest OSRAM truck light





Excellent brightness More light allows to see farther and therefore react sooner



More than double the service life Reduced downtime and fleet costs compared to standard lamps



Very high vibration resistance Suitable for heavy duty applications



The most powerful halogen truck light from OSRAM

Discover TRUCKSTAR PRO signal lamps - the brightest truck light from OSRAM with excellent value for money. With up to 100% more light than standard lamps, extremely long life and very high vibration resistance these 24 volt lamps are ideal for professional drivers while reducing downtime and fleet costs. Thanks to the high vibration resistance, TRUCKSTAR PRO lamps are suitable even for heavy duty applications. Due to their impressive brightness and more than double the service life compared to standard lamps, the lamps improve your safety while driving on the road.

Product datasheet

Technical data

Product information

Order reference	5627TSP
Application (Category and Product specific)	Auxiliary lamp


Electrical data

Power input	7 W
Nominal voltage	24.0 V
Nominal wattage	5.00 W
Power input tolerance	±10 %
Test voltage	28.0 V

Photometrical data

Luminous flux	50 lm
Luminous flux tolerance	±20 %

Dimensions & weight



Length	37.5 mm
Diameter	16.0 mm
Product weight	6.01 g

Lifespan

Lifespan B3	500 h
Lifespan Tc	1000 h

Additional product data

Base (standard designation)	BA15s
Suse (standard designation)	5,(155

Product datasheet

Capabilities

Technology	AUX	
Certificates & standards		
ECE category	R5W	
Country specific categorizations		
Order reference	5627TSP	

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321795151	TRUCKSTAR PRO R5W	Unpacked 1	139 mm x 42 mm x 57 mm	0.33 dm ³	71.00 g
4008321795168	TRUCKSTAR PRO R5W	Folding carton box 10	54 mm x 40 mm x 138 mm	0.30 dm ³	73.10 g
4008321795175	TRUCKSTAR PRO R5W	Shipping carton box 50	205 mm x 144 mm x 64 mm	1.89 dm³	427.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

ECE E1 approval

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.







1. 0 ℃ S 2. ⇐□ ↔ [



