Product datasheet

OSRAM ORIGINAL - GLASS WEDGE BASE W21/5W

Original spare part





The cost-effective original spare parts

The ORIGINAL signal lamps with glass wedge bases are available as original spare parts for different lamp types. Discover these reliable lamps and OSRAM's proven high quality.

Product datasheet

Technical data

Product information

Order reference	7515
Application (Category and Product specific)	Auxiliary lamp

Electrical data

Power input	25 / 6 W
Nominal voltage	12.0 V
Nominal wattage	21/5 W
Test voltage	13.5 V
Power input tolerance	±6 / ±10 %

Photometrical data

Luminous flux	440/35 lm
Luminous flux tolerance	±15 / ±20 %

Dimensions & weight





Diameter	20.0 mm
Product weight	6.80 g
Length	47.5 mm

Lifespan

Lifespan B3	250 / 600 h ¹⁾
Lifespan Tc	500 / 1600 h ¹⁾

¹⁾ Filament 1 / Filament 2

Additional product data

Base (standard designation)	W3x16q

Product datasheet

Capabilities

Technology	AUX
Certificates & standards	
ECE category	W21/5W
Country specific categorizations	
Order reference	7515

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899324312	ORIGINAL - WEDGE BASE W21/5W	Unpacked 1	- x - x -		
4052899324329	ORIGINAL - WEDGE BASE W21/5W	Folding carton box 10	58 mm x 54 mm x 139 mm	0.44 dm ³	96.00 g
4052899324336	ORIGINAL - WEDGE BASE W21/5W	Shipping carton box 50	273 mm x 145 mm x 65 mm	2.57 dm ³	567.00 g
4052899324589	ORIGINAL - WEDGE BASE W21/5W	Blister 2	95 mm x 70 mm x 28 mm	0.19 dm³	19.50 g
4052899324596	ORIGINAL - WEDGE BASE W21/5W	Shipping carton box 20	280 mm x 80 mm x 103 mm	2.31 dm³	266.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.







1.0 ℃ S 2. ⊂⊕ ↔ [





