OSRAM

LEDinspect PRO SLIMLINE 280

Professional LED inspection light





280 lm + 70 lm

This high-powered main light with 280 lumen comes with an additional torch function of 70 lumen



Equipped with 6+1 high-power, longlasting LEDs

High-power LEDs for long-lasting comfortable light output



Integrated battery status display

Cordless professional lighting tool with docking station



Professional inspection light with flexible design

LEDinspect PRO SLIMLINE 280 is a rechargeable LED inspection light with robust design. Thanks to the long-lasting high intensity LEDs with a color temperature of up to 6,000 Kelvin, this luminaire produces a powerful light for your garage. In addition to the high-powered main light, the durable fixture has a torch function and provides a 180° degree bending mechanism. No batteries are needed – LEDinspect PRO SLIMLINE 280 can be easily charged via USB port and DC connection. OSRAM offers a 3 year guarantee for this inspection luminaire.

Technical data

Product information

| Order reference | LEDIL103 |
|---------------------------------------------|-----------------------------------------|
| Application (Category and Product specific) | LED inspection lights for professionals |


Electrical data

| Nominal wattage | 3.5 W |
|-----------------|-------|
| Nominal voltage | 3.4 V |

Photometrical data

| Color temperature | 6000 K |
|-------------------|--------|
| Luminous flux | 280 lm |
| Light color LED | White |

Dimensions & weight



| Product weight | 374.00 g |
|----------------|----------|
| Length | 284.0 mm |
| Width | 37.0 mm |
| Height | 26.0 mm |

Colors & materials

| Base color | Orange/black |
|------------|--------------|
| | _ |

Lifespan

| Guarantee | 3 years |
|-----------|---------|

Additional product data

| Number of included batteries | n.a. |
|------------------------------|------------------------------|
| Scope of battery | Yes |
| Battery | Li-ion Polymer Battery Model |

Capabilities

| Technology | LED |
|------------|-----|

Certificates & standards

| Standards | CE |
|--------------------|------|
| Type of protection | IP44 |

Country specific categorizations

| Order reference | LEDIL103 |
|-----------------|----------|
|-----------------|----------|

Logistical data

| PCHL Watt hour per battery [MPRD] | 7.40 |
|-----------------------------------|------|
|-----------------------------------|------|

Equipment / Accessories

- Charging cable included







Detail Detail Detail



Detail

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|--------------------------------|---------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899327351 | LEDinspect PRO SLIMLINE 280 | Folding carton box 1 | 97 mm x 80 mm x 335 mm | 2.60 dm ³ | 442.74 g |
| 4052899327368 | LEDinspect PRO SLIMLINE 280 | Shipping carton box | 213 mm x 179 mm x 368 mm | 14.03 dm ³ | 2063.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| | File |
|---|--------------------------------------------------------|
| 太 | User instruction 730884_LEDinspect PRO SLIMLINE 280 |
| D | Movie application Image Film LEDinspect Pro (EN) |
| • | Movie application Image Film LEDinspect Family (EN) |

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM