



## TECHNICAL DATA / FEATURES

- dimensions: 105x105x50
- luminous flux of the LED module: 1600 lm, 800 lm
- luminous flux of the lamp: 1300 lm, 650 lm
- maximum power: 22W, 11W
- nominal voltage: 12V-24V DC
- permissible power supply voltage: 10.5V-30V DC
- source of light: 12 x LED, 6 x LED
- colour temperature: 4000-6000K
- light distribution angle: 28° x 28°, 50° x 30°
- IP rating: IP67, IP69K
- work temperature: -40°C - +80°C
- housing's material: aluminium
- lens' material: plastic
- built-in connectors: Deutsch DT, AMP SuperSeal 1.5
- other: protection:
  - against overheating
  - against reverse polarisation



## ADDITIONAL INFORMATION

Work lamps are used to illuminate working space near vehicles, tractors, slow-moving machines and any other places where indicated voltage is available.

The lamps comply with EMC Directive 2004/108/EC. They do not emit electromagnetic interference as well as they are resistant to it's influence.

Correct polarity required.

Mounting: as a freestanding on body panels. They can be installed in any position (standing, hanging, on side).

It is possible to install needed connectors for a version with cable (on request).

Useful parts while installing:



deutsch plug DT06-2S 2-pin - cat. No. A.07135

AMP SuperSeal 1,5 plug 2-pin - cat. No. A.07137

Equivalentents for Hella:

CRK2B.54200 - 1GA 011 720-041

## DIMENSIONS



Cat. number	Luminous flux 1600 lm 800 lm	Beam angle 28° x 28° 50° x 30°	housing black white	Accessories cable 0.5 m cable 8 m switch cigarette lighter plug	Bracket M8 omega neodymium magn.	Connectors Deutsch DT AMP SuperSeal 1.5	Packaging / pc carton box blister pack
<b>CRK2B.54200</b>	✓	✓	✓	✓	✓		1
CRK2B.54210	✓	✓	✓	✓	✓		1
CRK2B.54230	✓	✓	✓	✓	✓		1
<b>CRK2B.54206</b>	✓	✓	✓	✓	✓		1
CRK2B.54250	✓	✓	✓	✓	✓	✓	1
CRK2B.54270	✓	✓	✓	✓	✓	✓	1
<b>CRK2C.54900</b>	✓	✓	✓	✓	✓		1
CRK2C.54910	✓	✓	✓	✓	✓		1
CRK2C.54930	✓	✓	✓	✓	✓		1
CRK2C.54950	✓	✓	✓	✓	✓	✓	1
CRK2C.54970	✓	✓	✓	✓	✓		1
CRK2D.55700	✓	✓	✓	✓	✓	✓	1
CRK2D.55750	✓	✓	✓	✓	✓	✓	1
<b>CRK2A.54100</b>	✓	✓	✓	✓	✓		1
CRK2A.54110	✓	✓	✓	✓	✓		1
Cat. number	Luminous flux 1600 lm 800 lm	Beam angle 28° x 28° 50° x 30°	housing black white	Accessories cable 0.5 m cable 8 m switch cigarette lighter plug	Bracket M8 omega neodymium magn.	Connectors Deutsch DT AMP SuperSeal 1.5	Packaging / pc carton box blister pack
CRK2A.54130	✓	✓	✓	✓	✓		1
CRK2A.54150	✓	✓	✓	✓	✓		1
CRK2A.54170	✓	✓	✓	✓	✓		1
CRK2B.54240	✓	✓	✓	✓	✓		1
CRK2B.54260	✓	✓	✓	✓	✓		1
CRK2B.54280	✓	✓	✓	✓	✓		1
CRK2C.54940	✓	✓	✓	✓	✓		1
CRK2C.54960	✓	✓	✓	✓	✓		1
CRK2C.54980	✓	✓	✓	✓	✓		1
CRK2A.54140	✓	✓	✓	✓	✓	✓	1
CRK2A.54160	✓	✓	✓	✓	✓		1
CRK2A.54180	✓	✓	✓	✓	✓		1
CRK2B.54290	✓	✓	✓	✓	✓		1
CRK2C.54990	✓	✓	✓	✓	✓		1
CRK2A.54190	✓	✓	✓	✓	✓		1